

# HULK<sup>®</sup> SERIES LIFT TABLE

## L I F T P R O D U C T S S P E C I F I C A T I O N S

### Design Highlights

- Hand-held NEMA 4X Push Button with 10' Straight Cord
- Maintenance Strut
- Self Lubricating Bushings
- Wire Braided Hydraulic Hoses
- Solid Steel Legs with Hard Chromed Pins
- Pre-wired Power Unit with UL Approved Control Panel
- Velocity Fuses on All Cylinders to Prevent Uncontrolled Descent
- Polyethylene Reservoir Allows Easy Visual Check of Oil Level or Steel Reservoir with Dip Stick
- 1 HP Single Phase with 115 VAC Control Valve
- Meets or Exceeds the ANSI MH29.1 Standard for Industrial Scissors Lifts



### Available Options

- Oversized Platforms with Straight Sides
- Oversized Platform with Beveled Toe Guards. (Add 8" to Length and Width. Lowered Height Increases to 8 1/2")
- Accordion Skirting (Platform Must Be 6" Longer and Wider than Standard)
- Remote Air Operated Power Unit. Requires 70psi and 95cfm Clean Plant Air; Includes Hand Valve NEMA 4 Washdown Power Unit and Controls
- Increased HP Available
- 1 HP 3 Phase
- NEMA 12, Wall Mount Up/down Push Button Station
- Upper Travel Limit Switch
- High Cycle Package
- Wall Mount Push Button Station
- Foot Switch with Cover - NEMA 1
- Portability
- Other \_\_\_\_\_

### Project Information

Job Name \_\_\_\_\_

Address \_\_\_\_\_

General Contractor \_\_\_\_\_

Distributor \_\_\_\_\_

Model \_\_\_\_\_ Quantity \_\_\_\_\_ Voltage/Phase \_\_\_\_\_





# HULK<sup>®</sup> SERIES LIFT TABLE

## L I F T P R O D U C T S S P E C I F I C A T I O N S

Model No.	Travel [in]	Capacity [lb]	Standard Platform & Base Frame [in]	Maximum Platform Size [in]	Lowered Height [in]	Raised Height [in]	Raise Lower Time (sec)	Ship Weight [lb]
KLT24-2	24	2,000	24 x 36	48 x 58	7	31	18	455
KLT24-4		4,000	24 x 36	48 x 58	8	32	25	640
KLT24-6		6,000	30 x 36	48 x 58	8	32	54	780
KLT24-8		8,000	36 x 36	48 x 58	10	34	62	890
KLT36-2	36	2,000	24 x 48	48 x 60	7	43	24	619
KLT36-4		4,000	24 x 48	48 x 60	9	45	48	710
KLT36-6		6,000	30 x 48	48 x 60	9	45	72	970
KLT36-8		8,000	36 x 48	48 x 60	12	48	81	1,340
KLT48-2	48	2,000	24 x 72	48 x 96	8	56	35	960
KLT48-4		4,000	24 x 72	48 x 96	9	57	70	1,000
KLT48-6		6,000	30 x 72	48 x 96	9	57	105	1,430
KLT48-8		8,000	36 x 72	48 x 96	12	60	138	1,984
KLT48-10		10,000	36 x 72	48 x 96	12	60	154	2,144
KLT59-2	59	2,000	24 x 88	48 x 102	8	67	40	1,207
KLT59-4		4,000	24 x 88	48 x 102	9	68	80	1,470
KLT59-6		6,000	30 x 88	48 x 102	9	68	120	1,850
KLT59-8		8,000	36 x 88	48 x 102	12	71	159	2,540
KLT59-10		10,000	36 x 88	48 x 102	12	71	201	2,740