

HULK[®] SERIES RAIL LIFT

L I F T P R O D U C T S S P E C I F I C A T I O N S

Design Highlights

- Low Profile for Surface-mounted Applications
- No Pit Construction Required
- Three-sided Platform
- Heavy-duty I-beam Deck Understructure
- Excellent End-load Stability in Fully Raised Position
- Displacement style Cylinder with Internal Stops
- Self-contained Power Unit/control Panel
- Standard Pre-wired Control Panel
- NEMA 4X Push-button Controller with 15' Cord
- Superior Speed-to-horsepower Ratio Compared to Scissor-style Dock Lifts
- Direct thrust Cylinder Provide Constant Speed Through Full Range of Travel
- Checker Plate or Smooth Deck Surface
- Sealed Guide Bearing Rollers
- Fused 24-volt Control Circuit
- 18" Bridge
- 30" Stationary Ramp with Lagging Angles
- Bolt On Handrail
- Hydraulic System Pressure Gauge

Project Information

Job Name _____
Address _____
General Contractor _____
Distributor _____
Model _____ Quantity _____ Voltage/Phase _____



Available Options

- Upper Travel Limit Switch
- In Motor Warning Beeper and Flashing Light on a Post X 60" High or Wall Mounted on Bracket
- Interlocking Gate
- Aluminum Bridges
- Larger Steel Bridges
- Power Pack Cover
- Other _____



ENTRE/MATIC

HULK[®] SERIES RAIL LIFT

L I F T P R O D U C T S S P E C I F I C A T I O N S

Model No.	Lift Capacity [lbs.]	Deck Size [in]	Feet Per Minute [FPM]	HP	Ship. Weight [lb]
KRL45-4	4,000	48 x 60	13	5	2,050
KRL46-4	4,000	48 x 72	13	5	2,200
KRL55-4	4,000	60 x 60	13	5	2,150
KRL56-4	4,000	60 x 72	13	5	2,500
KRL57-4	4,000	60 x 84	13	5	2,650
KRL58-4	4,000	60 x 96	13	5	2,800
KRL66-4	4,000	72 x 72	13	5	2,800
KRL67-4	4,000	72 x 84	13	5	2,950
KRL68-4	4,000	72 x 96	13	5	3,100
KRL610-4	4,000	72 x 120	13	5	3,300
KRL612-4	4,000	72 x 144	13	5	3,600
KRL45-6	6,000	48 x 60	12	5	2,200
KRL46-6	6,000	48 x 72	12	5	2,400
KRL55-6	6,000	60 x 60	12	5	2,400
KRL56-6	6,000	60 x 72	12	5	2,750
KRL57-6	6,000	60 x 84	12	5	2,875
KRL58-6	6,000	60 x 96	12	5	3,000
KRL66-6	6,000	72 x 72	12	5	3,100
KRL67-6	6,000	72 x 84	12	5	3,250
KRL68-6	6,000	72 x 96	12	5	3,400
KRL610-6	6,000	72 x 120	12	5	3,700
SRL612-6	6,000	72 x 144	12	5	3,900



ENTRE/MATIC

1612 Hutton Drive, Suite 140 ▾ Carrollton, TX 75006, USA ▾ Tel: 800-558-6960 ▾ Fax: 972-389-4766 ▾ Email: sales@kelleycompany.com ▾ www.kelleycompany.com
 A continuing research program is in effect at Kelley. We reserve the right to incorporate product improvement at any time without prior notice.

© 2013 4Front Engineered Solutions, Inc.

Form # KPS-LDRL-1213