

Design Highlights

- High tensile strength, structural tubing construction for maximum stability
- Velocity fuses on lift cylinders prevent lift from free falling in the event of hydraulic failure
- Pre-wired NEMA-4X push button control panel
- Versatile, split entry plates with lifting chains and entry ramp
- Removable, mandrel formed tubing handrails
- Maintenance strut
- Removable lifting lugs
- Meets ANSI MH29.1 Safety requirements for industrial scissor lifts
- Upper travel limit switch
- Oil sight gauge in hydraulic reservoir
- Self-lubricating bushings
- Standard 25' hydraulic hose
- Low temperature oil
- Two-year parts, one-year labor limited warranty
- UL approved panel
- One (1) 24"l x 60" and one (1) 36" x 60" w split bridge plate with lifting chains
- Manual lowering valve use in power loss to lower lift



Available Options

- Portability
- Electric Toe Guards
- Aluminum Bridge Plates
- Post Office Option Package
- Hot Dipped Galvanized
- Spring-assisted Bridge
- In-motion Warning Beeper and Flashing Light
- Roller Curtains
- Accordion Bellow Skirting
- Mechanical Pop-up Stop
- Biodegradable Oil
- Special Sizes
- Other _____

Project Information

Job Name _____
 Address _____
 General Contractor _____
 Distributor _____
 Model _____ Quantity _____ Voltage/Phase _____

Certified For Construction

By _____
 Company _____
 Address _____
 Date _____



KELLEY KDL-SM DOCK LIFT

PRODUCT SPECIFICATIONS

SURFACE MOUNTED DOCK LIFT

ENTREMATIC

Model No.	Travel [in]	Capacity [lb]	Standard Platform [in]	Max. End Load [lb]	Max. Side Load [lb]	Lowered Height [in]	HP	Raise Lower Speed [fpm]	Ship Weight [lb]
KDL47-4SM	52	4,000	48 x 84	2,400	2,000	7	3	12	2,400
KDL47-5SM	52	5,000	48 x 84	3,000	2,500	7	3	10	2,550
KDL47-6SM	52	6,000	48 x 84	3,600	3,000	7	3	10	2,650
KDL57-4SM	52	4,000	60 x 84	2,400	2,000	7	3	15	2,500
KDL57-5SM	52	5,000	60 x 84	3,000	2,500	7	3	10	2,650
KDL57-6SM	52	6,000	60 x 84	3,600	3,000	7	3	10	2,750
KDL67-4SM	52	4,000	72 x 84	2,400	2,000	7	3	9	2,850
KDL68-5SM	52	5,000	72 x 96	2,500	2,500	7	3	9.5	2,850
KDL68-8SM	52	8,000	72 x 96	4,000	4,000	8	3	8	4,500
KDL610-5SM	52	5,000	72 x 120	2,500	2,500	7	3	8	3,500
KDL612-12SM	*52	6,000	72 x 144	6,000	6,000	8	10	9	6,500

* Includes 72 x 72 floor mounted entry ramp