

# HULK<sup>®</sup> SERIES LIFT AND TILT L I F T P R O D U C T S S P E C I F I C A T I O N S



## Design Highlights

- Hand-held NEMA 4X Push Button with 10' Straight Cord
- Hinged Maintenance Strut
- Self Lubricating Bushings
- Wire Braided Hydraulic Hoses
- Solid Steel Legs with Hard Chromed Pins
- Pre-wired Power Unit with UL Approved Control Panel
- Velocity Fuses on All Cylinders to Prevent Uncontrolled Descent
- Polyethylene Reservoir Allows Easy Visual Check of Oil Level or Steel Reservoir with Dip Stick
- 1 HP Single Phase with 115 VAC Control Valve
- Meets or Exceeds the ANSI MH29.1 Standard for Industrial Scissors Lifts and ANSI MH29.2 Standard for Tilters



Shown with Optional Accordion Skirting

## Available Options

- Up Travel Limit Switch
- Foot Switch with Cover - NEMA 1
- In Motor Warning Beeper and Flashing Light on a Post X 60" High or Wall Mounted Bracket
- Increased Horsepower Available
- Manual Lowering Valve Located at Power Pack
- 1 HP Air/hydraulic Power Unit with Air Lever Valve or Air Foot Valve and 10' of Hose  
1 HP 3 Phase Available
- Portability with Casters
- Stainless Steel
- Accordion Bellow - Yellow/black
- Hot Dip Galvanizing
- Special Color
- Other \_\_\_\_\_

## Project Information

Job Name \_\_\_\_\_  
 Address \_\_\_\_\_  
 General Contractor \_\_\_\_\_  
 Distributor \_\_\_\_\_  
 Model \_\_\_\_\_ Quantity \_\_\_\_\_ Voltage/Phase \_\_\_\_\_



# HULK<sup>®</sup> SERIES LIFT AND TILT

## L I F T P R O D U C T S S P E C I F I C A T I O N S

Model No.	Travel [in]	Capacity [lb]	Standard Platform & Base Frame [in]	Maximum Platform Size [in]	Tilt Angle [deg]	Lowered Height [in]	Raised Height [in]	Raise Lower Time (sec)	Ship Weight [lb]
KLT24-2T	24	2,000	24 x 36	48 x 58	45	16	40	18	961
KLT24-4T		4,000	24 x 36	48 x 58	45	17	41	25	1,160
KLT24-6T		6,000	30 x 36	48 x 58	45	17	41	54	1,380
KLT36-2T	36	2,000	24 x 48	48 x 60	45	16	52	24	1,210
KLT36-4T		4,000	24 x 48	48 x 60	45	18	54	48	1,320
KLT36-6T		6,000	30 x 48	48 x 60	45	18	54	72	1,430
KLT48-2T	48	2,000	24 x 72	48 x 96	45	17	65	35	1,700
KLT48-4T		4,000	24 x 72	48 x 96	45	18	66	70	1,760
KLT48-6T		6,000	30 x 72	48 x 96	45	18	66	105	2,290
KLT59-2T	59	2,000	24 x 88	48 x 102	45	17	76	40	2,067
KLT59-4T		4,000	24 x 88	48 x 102	45	18	77	80	2,400
KLT59-6T		6,000	30 x 88	48 x 102	45	18	77	120	2,880